


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		REMOVED SAFETY WIRE NOTCH AND ADDED NEW REVISIONS TABLE. CH'D MATERIAL FROM Ø2 O.D. AND NOTE 1 FROM SAW IN HALF W/ .060-.032 SAW.	6/26/2007	WP	DW
1A		CH'D TITLEBLOCK & REVISION BLOCK, ADDED ENGRAVE NOTE.	1/21/2010	RJC	RW
2	16-0026	CH'D ANGLE DIM WAS 7° IS {6.72°}.	2/8/2016	RJC	JAG
3	16-0152	CH'D P/N WAS RBT18803 IS RBT18803-1. -1 CH'D DESCRIPTION WAS BOOT INSTALL & REMOVAL TOOL IS BOOT REMOVAL TOOL; CH'D DIM WAS 1.057 IS 1.00, WAS 1.84 IS 2.000, WAS Ø.807 IS .825, WAS 2.00 IS 2.10, WAS .20 IS .25, WAS {6.72°} IS {7.83°}; REMOVED DIM .20 X 45°; ADDED DIM .19 X 45°, R.25, R.06. -3 ADDED TO ASSEMBLY.	9/27/2016	SM	JAG



DART
AEROSPACE

TITLE
BOOT INSTALL & REMOVAL TOOL

DWG NO. RBT18803 **REV** 3

MAT'L	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT	.XXX ± .005 FRACTIONS ± 1/8
TREAT	.XX ± .01 ANGLES ± 5°
FINISH	X ± .1 SURFACES = 125
SPEC	
DRAWN BY:	MACKOVJAK
CHECKED:	DUERFELDT
OPPS APPR:	ANDERSON
QA APPR:	LINDSAY
APPROVED:	GILBERT
SCALE	3:4
DATE	9/27/2016
USED ON MODEL	

1. BREAK ALL SHARP EDGES
.015 x 45° OR .015R




2. DIMENSIONAL LIMITS APPLY
AFTER PLATING

3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1 SET	BOOT REMOVAL TOOL	WHITE DELRIN		2
			-3	1	BOOT INSTALL TOOL	WHITE DELRIN		3

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		REMOVED SAFETY WIRE NOTCH AND ADDED NEW REVISIONS TABLE. CH'D MATERIAL FROM Ø2 O.D. AND NOTE 1 FROM SAW IN HALF W/.060-.032 SAW.	6/26/2007	WP	DW
1A		CH'D TITLEBLOCK & REVISION BLOCK, ADDED ENGRAVE NOTE.	1/21/2010	RJC	RW
2	16-0026	CH'D ANGLE DIM WAS 7° IS (6.72°).	2/8/2016	RJC	JAG
3	16-0152	-1 CH'D DESCRIPTION WAS BOOT INSTALL & REMOVAL TOOL IS BOOT REMOVAL TOOL; CH'D DIM WAS 1.057 IS 1.00, WAS 1.84 IS 2.000, WAS Ø.807 IS .825, WAS 2.00 IS 2.10, WAS .20 IS .25, WAS (6.72°) IS (7.83°); REMOVED DIM .20 X 45°; ADDED DIM .19 X 45°, R.25, R.06.	9/28/2016	SM	JAG



(-1)

BOOT REMOVAL TOOL

NOTE:
1 SAW IN HALF AND MILL BEFORE TURNING.

DART
AEROSPACE

TITLE		BOOT INSTALL & REMOVAL TOOL	REV
DWG NO.		RBT18803-1	3
MATERIAL		WHITE DELRIN	
HEAT TREAT		.XXX ± .005 FRACTIONS ± 1/8	
FINISH		.XX ± .01 ANGLES ± 5°	
SPEC		X ± .1 SURFACES = 125 ✓	
DRAWN BY:		PERRITT	
CHECKED:		DUERFELDT	
OPPS APPR:		ANDERSON	
QA APPR:		LINDSAY	
APPROVED:		GILBERT	
SCALE		3:4	DATE
DATE		7/1/2005	SHEET 2 OF 3

USED ON MODEL

269



1. BREAK ALL SHARP EDGES
.015 x 45° OR .015R

2. DIMENSIONAL LIMITS APPLY
AFTER PLATING

3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REV			ECR			DESCRIPTION			REVISIONS		
3	16-0152	-3 ADDED TO ASSEMBLY.							DATE	INITIAL	APPROVED
									9/28/2016	SM	JAG



(-3)

BOOT INSTALL TOOL

DART AEROSPACE	
TITLE	
BOOT INSTALL & REMOVAL TOOL	
DWG NO.	
RBT18803-3	
REV 3	
MATERIAL: WHITE DELRIN	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
HEAT	.XXX ± .005 FRACTIONS ± 1/8
TREAT	.XX ± .01 ANGLES ± 5°
FINISH	X ± .1 SURFACES = 125 ✓
SPEC	
DRAWN BY:	MACKOVJAK
CHECKED:	DUERFELDT
OPPS APPR:	ANDERSON
QA APPR:	LINDSAY
APPROVED:	GILBERT
USED ON MODEL	
269	
SCALE	3:4
DATE	9/27/2016
SHEET 3 OF 3	